

WEATHERMASTER X-TREME FOAM™

INSTALLATION IN 3 EASY STEPS

STEP 1

Be sure the product in the can is mixed very well before using. The propellant is not completely soluble in the polyurethane and separation will occur. Mixing vigorously is the only way to make sure the propellant will come out with the polyurethane resin and the product will foam up properly.

User Tip: The resin has the consistency of honey and the propellant resembles water so shake the can as hard as you would to mix honey and water together.

STEP 2

12 oz. - Attach straw, invert the can and begin dispensing.

24 oz. - Attach the can to the Dispensing Unit and begin dispensing.

User Tip: Initially fill joint 1/3 of the way so that the foam does not expand out of the cavity.

STEP 3

Reapply foam, if necessary, once it has cured – the foam will bond to itself.

User Tip: Shaking the can in between sprays is recommended to keep the mixture as uniform as possible.





DISPENSING UNIT MAINTENANCE

To keep your Dispensing Unit working longer, be sure to NOT remove the can from the Dispensing Unit when storing it!

STEP 1

Load the can onto the Dispensing Unit – be sure to screw the Dispensing Unit on the can upside down.

User Tip: Make sure control valve is closed when screwing the can on the Dispensing Unit.

STEP 2

Use the foam for your job.

User Tip: Be sure to wipe the foam from the Dispensing Unit's tip every time you stop spraying to prevent the foam from drying on the tip and clogging the Dispensing Unit.

STEP 3

That's it! Just leave the can on the Dispensing Unit for storage. Keep the trigger from being inadvertently pressed during storage by confirming that the trigger adjustment is cinched tight.

User Tip: If changing cans, especially before storing Dispensing Unit overnight, purge enough foam from the Dispensing Unit to eliminate any foam that was exposed to moisture in the air during can change.

STEP 4

If the Dispensing Unit needs to be cleaned, use X-treme Foam Cleaner to purge foam and clean tip and basket.

User Tip: Leave can of X-treme Foam Cleaner on the Dispensing Unit until ready to attach another foam can. After changing cans and before storage, purge enough foam through the Dispensing Unit to eliminate any moist air that may have entered the Dispensing Unit during foam can change over.

And again, store your Dispensing Unit with a can still screwed on to the Dispensing Unit with the control valve closed.

VISIT WWW.TITEBOND.COM FOR THE MOST UP-TO-DATE PRODUCT INFORMATION

